

(12) United States Patent

Nolan

US 9,409,795 B2 (10) Patent No.:

(45) **Date of Patent:** *Aug. 9, 2016

(54) WATER DISTRIBUTION SYSTEM WITH **DUAL USE WATER TREATMENT UNIT**

Applicant: INTERNATIONAL WATER-GUARD

INDUSTRIES, INC., Burnaby (CA)

(72)Inventor: Peter Daniel Nolan, North Vancouver

Assignee: INTERNATIONAL WATER-GUARD

INDUSTRIES, INC., Burnaby, B.C.

(CA)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 412 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 13/941,771

Filed: (22)Jul. 15, 2013

(65)**Prior Publication Data**

> US 2013/0298998 A1 Nov. 14, 2013

Related U.S. Application Data

- Continuation of application No. 12/628,752, filed on Dec. 1, 2009, now Pat. No. 8,568,585.
- Provisional application No. 61/193,453, filed on Dec. 1, 2008.
- (51) Int. Cl. B01D 35/027 (2006.01)(2006.01)B01D 35/157

(Continued)

(52) U.S. Cl.

CPC C02F 1/006 (2013.01); B01D 35/027 (2013.01); **B01D** 35/157 (2013.01); **B01D** 36/04 (2013.01);

(Continued)

(58) Field of Classification Search

CPC B01D 21/30; B01D 35/02; B01D 35/027; B01D 35/153; B01D 35/157; B01D 35/1573; B01D 36/00; B01D 36/04; B01D 2201/16; B01D 2201/165; B01D 2201/167; B01D

2221/08; B01D 2221/265; C02F 1/001; C02F 1/006; C02F 1/20; C02F 1/283; C02F 1/32; C02F 1/325; C02F 2201/001; C02F 2201/005; C02F 2201/326; C02F 2301/04; C02F 2301/043; C02F 2301/046 USPC 210/134, 141, 143, 192, 167.01, 172.1, 210/172.6, 194, 195.1, 205, 120, 257.1, 210/257.2, 258, 259, 335, 416.1, 418, 420, 210/424, 760, 764, 109, 110, 117, 136, 210/248; 137/565.01, 565.26, 571, 624.11, 137/625.18; 222/52, 63, 64, 189.06, 189.11 See application file for complete search history.

References Cited (56)

U.S. PATENT DOCUMENTS

2,932,331 A 4/1960 Reed 6/1960 Crane 2,940,595 A (Continued)

OTHER PUBLICATIONS

Office Action in related Canadian Patent Application No. 2,686,836, mailed Nov. 3, 2015.

Primary Examiner — Joseph Drodge (74) Attorney, Agent, or Firm — Troutman Sanders LLP; Ryan A. Schneider; Christopher C. Close, Jr.

(57)ABSTRACT

A water distribution system having a dual use water treatment unit. The same water treatment unit can be used to treat water supplied from a fill port to a storage tank during a fill operation, as well as water leaving the storage tank for supply to one or more points of water use during a supply operation. When a diverter valve is in a fill position, water supplied to the fill port can flow through the diverter valve and to the water treatment unit for treatment then to the storage tank for storage. When the diverter valve is in a supply position, the water from the storage tank can be delivered using means for pressurizing water to the same treatment unit for treatment, then through the diverter valve and to a point of water use device.

26 Claims, 5 Drawing Sheets

